

RonaBond Masonry Coating WB

Water based masonry paint for internal and external use



FEATURES

- decorative and protective paint
- for use on most building surfaces
- two coat application
- suitable for internal and external application
- available in more than 150 pastel shades
- water based for safe application

Description

RonaBond Masonry Coating WB is a matt finish water based paint for internal and external decoration and protective maintenance. It can be applied to suitably prepared building surfaces including concrete and render. It has high opacity, is quick drying for same day recoating and is easy to use. It is water based with low odour and is non-flammable.

RonaBond Masonry Coating WB is ideally suited to wall, beam and soffit application in car parks to provide protection to concrete and improve overall appearance, light balance and reflection.

Physical Properties

Description	semi viscous paint
Dry film appearance	protective matt
Viscosity	120± 3KU
Total solids	by weight 61± 2%
	by volume 40± 2%
Density	1.56± 0.05
Coverage	8m ² per litre
Number of coats	2
Method Application	long pile roller, airless spray gun
Flashpoint	none
Drying times	
surface dry	30 minutes
recoatable	2 hours

Colours

RonaBond Masonry Coating WB is delivered to site ready to use. It is available in a wide range of pastel colours including base 0 colours prefixed 'STD' on the Zolpachrom colour swatch and base 0 colours prefixed 'FAC' on the Zolpachrom

RonaBond Masonry Coating WB

Water based masonry paint for internal and external use

Colours (continued) colour card. These colours are produced and pigmented and despatched from stock by Ronacrete in the UK.

Applied by a special roller, brush, conventional or airless spray RonaBond Masonry Coating WB is water based for safety in application. It can be applied to most suitably prepared (and primed if necessary) surfaces.

Limitations

- RonaBond Masonry Coating WB is not an elastomeric coating
- apply at ambient temperatures between 5°C and 35°C
- avoid application in strong direct sunlight or strong drying winds

Instructions for Use

1. prepare substrate by suitable means to provide a sound and stable surface. If necessary apply RonaBond Fungicidal Treatment to kill mould growth.
2. as required, apply metal or wood primers to dry surface and allow to dry (typically for 12 hours)
3. apply a first coat of RonaBond Masonry Coating WB diluted, when applying to bare surfaces, with 5-10% water at 8m² per litre and allow to dry.
4. apply a second coat of RonaBond Masonry Coating WB, undiluted, at 8m² per litre and allow to dry. Note that both coats should be the same colour.
5. RonaBond Masonry Coating WB is touch dry after 30 minutes and can be overcoated in 2 hours (longer in cold and/or damp conditions).
6. coverage rates will vary according to substrate type, porosity and texture.

RonaBond Masonry Coating WB can be applied using airless spray. The nozzle size shall be 619-621. Included within the spray should be a 60 mesh filter. Dilution of the coating can be made with water between 2-10%. Coverage on to smooth surfaces will be 8m² per litre per coat.

Cleaning tools and equipment Application equipment should be washed in clean water immediately after use.

Site attendance

When on site Ronacrete representatives are able, if asked, to give a general indication of the correct method of installing a Ronacrete product. It is important to bear in mind that Ronacrete Ltd is a manufacturer and not an application contractor and it is therefore the responsibility of the contractor and his employer to ensure he is aware of and implements the correct practices and procedures to ensure the correct installation of the product and that liability for its correct installation lies with the contractor and not with Ronacrete Ltd.

Packaging

RonaBond Masonry Coating WB is supplied in 16 litre tins.

RonaBond Masonry Coating WB

Water based masonry paint for internal and external use

Shelf life and storage

Store in frost free conditions away from direct heat and sunlight. Shelf life in unopened tins is 12 months

Health and safety

Non-toxic and non-hazardous; see health and safety data.

The information detailed in this leaflet is liable to modification from time to time in the light of experience and of normal product application, and before using, customers are advised to check with Ronacrete Ltd, quoting the reference number, that they possess the latest issue. Any person or company using the product without first making further enquiries as to the suitability of the product for the intended use does so at his own risk, and Ronacrete Ltd can accept no responsibility for the performance of the product, or for any loss or damage arising out of such use.