



...the choice matters

Electro safe MD550 Electrical switchboard matting

www.matsdirect.co.uk

Electrical Rubber matting fully Tested in Accordance with BS921/1976 British Standard and stamped on the reverse every 100cm.

A high quality Electrical Rubber safety matting made to exacting standards and fully certified and tested to 15,000v. Working volt test 650v.

Also available made specially to order to meet the following specifications:-

BS476: Part 7 1997 class 1 Flame resistance.

BS6853:1999 Annex B.2 Class 1a Smoke Toxicity.

BS6853:1999 Annex D.8.6 Class 1a Smoke Density.



Colour: Black
Hardness: 60 shore
Tensile: 5.0 Mp
Elongation 250%
Temperature Range: -20/+70DegC
Abrasion Resistance: 180 mm3

Thickness: 9.5mm
Roll size (10m x 1m): EX STOCK
Roll size (10mx 1.2m): EX STOCK
Weight/ M2 (kgs - appx): 12

MD550 Electrical Matting Performance.

- Fully branded on reverse
- Protection from electrical shock
- Hard wearing
- Positive safe grip from the flutes.

Cleaning and Maintenance:

Matting may be washed with soap or a mild non-bleaching detergent. After washing, the matting should be rinsed thoroughly with water.
Matting should be air dried, but not such that the matting temperature exceeds 65°C.

MatsDirect UK Ltd
Unit 2 Bolholt Industrial Park
Walshaw Road
Bury, Lancashire
BL8 1PL UK

For all enquiries:

Tel: 0044 (0)161-797-6785
Fax: 0044 (0)161-797-6349
E-mail: sales@matsdirect.co.uk